AMENDMENTS TO THE CLAIMS

Please AMEND claim 1 as shown below.

Please CANCEL claim 7.

The following is a complete list of all claims in this application.

- 1. (Currently Amended) A piezoelectric ink jet printer head formed by laminating a plurality of plates, the piezoelectric ink jet printer head including:
- a) an actuator portion being composed of upper and lower electrodes, a piezoelectric plate inserted between the upper and lower electrodes, a protection layer placed on the upper electrode, and a resilient plate disposed beneath the lower electrode;
- b) an ink passage portion composed of a spacer disposed beneath the resilient plate and forming a side portion of a chamber, a channel plate disposed beneath the spacer, the channel plate forming an ink passage in one side of the chamber and simultaneously expanding the chamber, and a nozzle plate disposed beneath the channel plate, the nozzle plate forming the lower side of the chamber and having a nozzle communicating with the chamber; and
- c) an ink-supplying portion formed by a through-hole reaching the ink passage of the channel plate through the actuator portion and the spacer, wherein the through-hole is through the actuator portion.

- 2. (Original) A piezoelectric ink jet printer head according to claim 1, wherein a tapered portion is formed at the upper part the nozzle such that the cross section of the chamber varies from the chamber to the starting point of the nozzle.
- 3. (Previously Presented) A piezoelectric ink jet printer head according to claim 1, wherein the ink jet printer head is provided with an ink container above the protection layer, wherein a plurality of ink jet head modules are arrayed on a same plane in a matrix fashion, each module being composed of the actuator portion, the ink passage portion and the ink-supplying portion, and wherein ink is supplied to the chamber of each ink jet head module from the ink container through each through-hole and ink passage.
- 4. (Previously Presented) A piezoelectric ink jet printer head according to claim 1, wherein the resilient plate is formed of ZrO₂.
- 5. (Previously Presented) A piezoelectric ink jet printer head according to claim 1, wherein the resilient plate is formed of BaTiO₃.
- 6. (Previously Presented) A piezoelectric ink jet printer head according to claim 1, wherein the resilient plate is formed of Al_2O_3 .

7. (Canceled)

- 8. (Previously Presented) A piezoelectric ink jet printer head according to claim 2, wherein the ink jet printer head is provided with an ink container above the protection layer, wherein a plurality of elementary ink jet head modules are arrayed in a same plane in a matrix fashion, each module being composed of the actuator portion, the ink passage portion and the ink-supplying portion, and wherein ink is supplied to the chamber of each elementary ink jet head module from the ink container through each through-hole and ink passage.
- 9. (Previously Presented) A piezoelectric ink jet printer head according to claim 2, wherein the resilient plate is formed of ZrO₂.
- 10. (Previously Presented) A piezoelectric ink jet printer head according to claim 2, wherein the resilient plate is formed of BaTiO₃.
- 11. (Previously Presented) A piezoelectric ink jet printer head according to claim2, wherein the resilient plate is formed of Al₂O₃.